

MODEL		U.M	GWH09AAB-K3DNA5A	GWH12AAB-K3DNA5A	GWH18AAD-K3DNA5E	GWH24AAD-K3DNA5A
Funcție			Racire/incalzire	Racire/incalzire	Racire/incalzire	Racire/incalzire
Capacitate min/nom/max	Racire	Btu/h	1700/8530/11500	2050/10920/12970	2220/15700/17750	5970/21000/21500
	Incalzire	Btu/h	2050/9385/12000	2050/11150/12970	2390/17060/18000	5970/21150/23030
SEER/SCOP (W/W)		W/W	6.10/4.0	6.10/4.0	6.10/ 4.0	6.10/4.0
Clasa de energie	Racire/incalzire		A++/A+	A++/A+	A++/A+	A++/A+
Alimentare		(Ph-V-Hz)	(1 Ph-220V-240V-50Hz)	(1 Ph-220V-240V-50Hz)	(1 Ph-220V-240V-50Hz)	(1 Ph-220V-240V-50Hz)
Putere electrica min/nom/max	Racire	W	160/790/1350	120/995/1400	150/1430/17860	450/2000/2200
	Incalzire	W	200/650/1450	120/1000/1500	160/1380/1680	450/1900/2430
Curent Nominal	Racire	A	3.45	4.4	6.34	9.35
	Incalzire	A	2.95	4.4	6.12	10
Debit de aer	SH/H/M/L	m3/h	500/500/430/300	550/500/430/300	850/720/610/520	850/720/610/520
Capacitate dezumidificare		L/h	0.8	1.4	1.8	2
Interval temperatura ext. de functionare (Min-Max)	Racire	°c	-15/+43	-15/+43	( -15, +48)	(-15, +43)
	Incalzire	°c	-15/+24	-15/+24	( -15, +24)	( -15, +24)
UNITATE INTERIOARA						
Nivel de Presiune Acustica	SH/H/M/L	dB/A	40/37/35/28	40/36/33/29	45/42/37/33	47/43/39/34
Nivel de putere Acustica			54/49/47/40	55/48/45/41	58/53/50/45	59/55/51/46
Dimensiune neta	LxlxH	mm	773x250x185	773x250x185	970x300x225	970x300x225
Greutate neta/bruta		kg	8.5/9.5	8.5/9.5	13.5/16.5	13.5/16.5
UNITATE EXTERIOARA						
Nivel de Presiune Acustica		dB/A	50	52	54	57
Nivel de putere Acustica			60	62	63	67
Dimensiune neta	LxlxH	mm	776x540x320	848/596/320	842x596x320	955x700x396
Greutate neta/bruta		kg	26/28.5	31/34	33/36	46/50.5
Traseu frigorific						
Diametru (lichid/gaz)		mm	6/9.52	6/9.52	6/9.52	6/16
Lungime maxima		m	15	20	20	25
Diferenta maxima de nivel		m	10	10	10	10